

Configurable Weighing Indicator

21e is built to answer the needs of highly demanding applications in the aspect of transaction & data speed, number of peripheral connections, management data & security, the flexibility of operation, and flexibility of future expansion. Maximum AD conversion speeds up to 480 times per second plus 9 filter strength levels to meet almost all requirements from high-resolution static weighing to high-speed dynamic applications. User-definable PC output protocol means the unsurpassed capability to meet all data format requirements from remote displays, and production management to ERP systems. Built-in non-resettable memory to store all details of up to 130,000+ transactions. Daily, monthly, and specific period reports can be recalled and generated anytime according to your search criteria.

Independently Configurable Function Modes:

- Static & Dynamic Weighing
- Piece Counting
- Action-Tare-Memory (ATM)
- Peak Measuring
- Grading and Sorting up to 10 Set Points and 8 Grades
- Checking Function for Weighing, Piece Counting, ATM, Grading, and Sorting Function

Management Features:

- 130000+ Non-Resettable Transaction Memory
- Daily, Monthly, specific Period Report Output
- Multi Search Criteria for Report Generation
- Configurable Machine ID, Machine Group and Operator Number to Enhance Ease of Multi Scales Applications and Management Records
- Customer & Product Code Input through Serial Scanner, Keypad or Barcode Reader
- Customer & Product Code Support Numbers, Alphabets and Selected Symbols
- Quick Access PLUs for Weight Limits, Quantity Limits and Preset Tare Values
- Direct PLUs for Customer & Product Codes
- Check Result Control for Accumulation, Data Printout & Data Output
- Keypad Lock Function
- Support Inquiry, Setting and Execution Commands from PC
- All Current Operation Results Output in Data Base Format Increases Ease & Efficiency of Data Management, Processing & Analysis
- Support Ticket Printer and Label Printer (Datecs LP-50 & TSC TDP-225, TDP-247, TDP-345, TTP225, TTP-247, TTP-345)
- Selectable Portrait / Landscape Ticket Printout Format



Options:

- Stainless Steel Wall/Desk Mount Holder
- SP-POS58IV & SP-POS88IV Thermal Ticket Printer
- LP-50, TDP-225, TTP-225, TTP-247, TTP-345 Label Printer
- Serial Barcode Reader
- WM Wireless Communication Module
- RD-DOT Dot Matrix Remote Display
- Bluetooth 4.0BLE Module □ Bluetooth 2.0 Module
- Isolated RS232
- Built-in 8-Channel Control Relay Board (Factory Installation)
- WIFI Module
- DPP-250 Bluetooth Thermal Printer













Global Asia Trading Company

Local agent of Fidelity Measurement Co. Ltd.,

 Website
 : www.gatcobd.com

 E-Mail
 : info@gatcobd.com

 Contact
 : +88 01711 531 809