



### Specifications:

Model Platform	Capacity (kg)	Platform Size (mm)	Load Cell Data				
			E <sub>max</sub> (kg)	IP Rating	V <sub>min</sub>		
FM-KB6	6	300 x 400	15	IP66	E <sub>max</sub> /15000		
FM-KB15	15		30				
FM-KB30	30		50	IP66	E <sub>max</sub> /9000		
FM-KB60	60		100				
FM-KB150	150		200				
FM-KF60	60	400 x 500	100	IP68	E <sub>max</sub> /10000		
FM-KF150	150		200				
FM-KF300	300		400				
FM-KL60	60	500 x 650	100			IP68	E <sub>max</sub> /10000
FM-KL150	150		200				
FM-KL300	300		400				
Operating Environment		-10~40°C(14~104°F) Non-condensed R.H. ≤85%					

### Key Features:

- #304 Stainless Steel Construction, Platter and Pillar (Optional)
- Equipped with OIML C3 Approved 17-4PH Stainless Steel Load Cell
- Complete Sealed Design, to Prevent Liquid Penetrate into Platform Structure
- Rugged Structure for Harsh and Rugged Environment
- Overload Protection Devices to Withstand Shock and Overloads
- Safe Overload = 150% plus
- Ultimate Overload = 200% plus
- Adjustable Feet and Bubble Level Included

### Options:

- All Grade #304 Stainless Steel Pillar
- FM16S Stainless Steel Weighing Indicator